COLORband Q4 IP

- Outdoor-rated LED strip light functions as a 4-zone effect, blinder or wall washer for any temporary outdoor event
- Weatherproof fixture designed for use at outdoor parties or behind wet bars
- Robust housing repels water, snow, dirt, and sand for all-weather applications
- · Password protected and touch-sensitive digital display
- Reduce cable clutter and link multiple units with the powerCON® TRUE1 connections
- Prevent internal humidity build-up and allow the fixture to breathe with the integrated GORE® valve
- Achieve flicker-free video operation with high-frequency LED dimming
- Easily transports in the optional CHS-60 VIP gear bag



Specifications

• DMX Channels: 4, 7, 10, 16, 22

DMX Connectors: 3-pin XLR
Light Course 40 LEDs (supple)

 Light Source: 12 LEDs (quad-color RGBA) 6 W, (2.06 A), 50,000 hours life expectancy

• Strobe Rate: 0 to 20 Hz

Beam Angle: 14°Field Angle: 27°

Illuminance: 7,074 lux @ 2 m, 1,209 lux @ 5 m

Lumens: 2,923IP Rating: IP65

• Startup Temperature: -4 °F to 113 °F (-20 °C to 45 °C)

Operating Temperature: -22 °F to 113 °F (-30 °C to 45 °C)

• Cable Length: 5 ft (1.5 m)

Power Linking: 9 units @ 120 V; 16 units @ 230 V

Input Voltage: 100 to 240 VAC, 50/60 Hz (auto-ranging)

Power and Current: 87 W, 1.18 A @ 120 V, 60 Hz

Power and Current: 86 W, 0.67 A @ 230 V, 50 Hz

• Weight: 11.8 lb (5.35 kg)

• Size: 39.3 x 3.2 x 4.1 in (998 x 81 x 104 mm)

· Approvals: CE, MET



